PROBEWARE INVESTIGATION 19 • A

In this investigation, you will construct various galvanic cells. The oxidation half-reaction occurs at the anode in one half-cell, and the reduction half-reaction occurs at the cathode in the other halfcell. The two half-cell reactions are separated, with a porous cup as the barrier between the two half-cells.

Question

What maximum voltages will be created by the galvanic cells?

Prediction

How many galvanic cells can be made from the following half-cells? Predict the identity of the anode and the cathode for each galvanic cell.

- $\operatorname{Cu} | \operatorname{Cu}^{2+}$
- $\operatorname{Zn} | \operatorname{Zn}^{2+}$
- $Pb | Pb^{2+}$

Materials

computer system and interface
voltage sensor
2 beakers (250 mL)
2 porous cups
50 mL of 0.5 mol/L Cu(NO₃)₂•3H₂O
50 mL of 0.5 mol/L Zn(NO₃)₂•6H₂O
50 mL of 0.5 mol/L Pb(NO₃)₂
1 cm × 8 cm copper, lead, and zinc metal strips (each strip must be free of oxidation)
clean cloth

Safety Precautions



• Wear safety goggles, gloves, and a lab coat while carrying out this investigation.

- Carry out the investigation carefully, to avoid broken glass.
- Wash your hands thoroughly after handling lead or lead compounds.
- Dispose of chemicals safely and appropriately, as directed by your teacher.

Procedure

Part 1

1. Set up the computer system with the voltage sensor set to record at a rate of once per second.

2. Display the digits and/or meter.

3. Place 20 mL of the Zn^{2+} solution in a 250 mL beaker.

4. Immerse the strip of Zn metal in the solution. This is the $Zn|Zn^{2+}$ half-cell.

5. Fill the porous cup to a depth of 2 cm with the Cu^{2+} solution.

6. Place the strip of copper metal in the solution to complete the $Cu|Cu^{2+}$ half-cell.

7. Connect one wire of the voltage sensor to the zinc metal strip, and the other wire to the copper metal strip.

8. Start the data recording.

9. Pick up the porous cup assembly and momentarily touch it to the solution in the beaker. If the voltage reading is negative, reverse the voltage sensor connections to the two metal strips.

Galvanic Cells

10. Place the porous cup into the 250 mL beaker and read the voltage immediately. (The electrodes become polarized and the voltage drops in a very short period of time.)

11. Remove the porous cup from the Zn^{2+} solution.

12. Thoroughly clean the copper metal strip used for the electrode. Rinse the outside of the porous cup with distilled water, and then dry it with a clean cloth. Replace the copper strip in the porous cup.

Part 2

13. In another 250 mL beaker, prepare a $Pb|Pb^{2+}$ half-cell using the Pb^{2+} solution and the lead strip.

14. Disconnect the voltage sensor wire from the zinc metal strip and attach it to the lead metal strip.

15. Repeat steps 9 and 10.

16. Remove the porous cup from the Pb^{2+} solution.

Part 3

17. In another porous cup, set up a $Zn \mid Zn^{2+}$ half-cell.

18. Disconnect the voltage sensor wire from the copper metal strip and attach it to the zinc metal strip.

19. Repeat steps 9 and 10.

20. Stop recording the data.

21. Clean up and discard the materials as directed by your teacher. Do not pour anything down the drain.

Analysis and Conclusions

1. Write a balanced equation for the overall cell reaction for each cell prepared in this investigation. Indicate the substance that is oxidized and the substance that is reduced in each reaction.

2. Calculate the voltages for each cell reaction using a table of standard reduction potentials.

3. What is the purpose of the porous cup?

4. Compare the cell potentials you calculated in question 2 with your experimental results. Give reasons for any differences you observe.

5. What are the standard conditions for measuring a cell potential?

Applications

6. What effect would changing the concentration have on cell voltages?